

# **QUICSEAL 634**

Product Name

# **Stone Impregnator**

### **Description**

QUICSEAL 634 is a water-based, water repellent impregnator that does not change the aesthetics of the surface and substrate. When applied, the product gives the surface an invisible protection and resistance against wear due to weathering factors.

#### Uses

QUICSEAL 634 is suitable for application on six sides of natural marbles, as well as materials such as cement, gypsum, limestone, bricks, roof tiles, agglomerates etc

# **Advantages**

- Oil, dirt and water repellent.
- Protects and does not alter the appearance of the stone.
- Can be applied on all six sides of marbles

## **Application**

QUICSEAL 634 should be applied when surface is very dry and clean. The impregnator should be applied using a short-haired roller, polish spreader or flat brush. Curing time is 24 hours. Two coats may be required depending on porosity of materials.

#### Accidental leakage and waste disposal method

In case material is released or spilled, clean up the most of the product. Absorb all residues with sand, sawdust etc. Store the residue in plastic tank and call for a specialized company.

#### **Packaging**

QUICSEAL 634 is supplied in 1 litre bottle, 5 litres drum and 25 litres drum.

#### Storage

Keep the tin closed and store in a cool place.

#### Shelf life

12 months

#### Coverage

30m<sup>2</sup> per litre per coat for polished stones 15 to 20m<sup>2</sup> per litre per coat for natural finished stones

#### **Important Notes**

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL

Reference No. QS634/280214