



QUICSEAL 646

Product Name

Hydro-adhesive

Description

QUICSEAL 646 is a specially formulated water-based adhesive for bonding a wide range of substrates.

Uses

- Bonding QUICSEAL 406 Polycel Type K to concrete or masonry substrate.
- Adhering PVC backed carpet tiles, PVC Film, glazed tiles, metal, plastic etc. substrates

Substrate Preparation

The substrates must be clean and sound, free of dust and loose particles. All loose particles, oil, grease, paint, wax or any substance that may inhibit adhesion must be removed.

Apply a thin layer of QUICSEAL 646 evenly by roller or brush. Allow drying for 15 to 20 minutes before pressing applied surfaces together to ensure full contact.

Technical Data

Product Type	Liquid
Colour	Milky white
Density of Mix	1.01 g/ml
Viscosity (Rion Viscometer)	17 Poise
Flash Point	Not Applicable

Coverage

Approximately 10-16m² per kg

Cleaning

Rinse hands and tools with abundant amount of water.

Packaging

QUICSEAL 646 is supplied in 5, 20 kg pails.

Storage

Shelf life of QUICSEAL 646 is 6 months if stored at temperatures between 4°C – 30°C

Important Notes

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL

Reference No. QS 646/040805

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

QUICSEAL – the professional's choice of quality products and systems for building construction