

QUICSEAL 654

Product Name

0 - Rus

Description

QUICSEAL 654 is a special product formulated to remove iron oxide from stones. QUICSEAL 654 removes iron oxide (rust) stains on unpolished stones and polished granite. The product is effective either for superficial stains due to contact of metallic objects with the surface of the stone or iron oxide already existent inside the stone.

Use

The product can be used on polished and unpolished granite, unpolished natural stones, sandstone, limestone and porcelain stoneware (homogeneous tile).

Technical Data

Appearance Transparent liquid

Colourless Colourless

PH (5% solution) 2 ~ 3

Density (20°C) 1.10 -1.15 g/ml

Biodegradability 90% (artt. 2 e 4 L.26.04.1983 n. 136

Application

Apply QUICSEAL 654 evenly onto the surface. Allow to act for several minutes or more until the stain have been removed the rinse with water. When the surface is dry, apply thin a thin coat of QUICSEAL 630s impregnator to prevent further oxidation.

Note: Always make a preliminary test to check stone resistance to the product. QUICSEAL 654 can be also used on marble and stones sensible to acids only in the working place before grinding and polishing.

Coverage

N/A

Packing

QUICSEAL 654 is supplied in 500ml & 1 litre bottle.

Shelf life

24 ~ 36 months when kept in a cool and ventilated place in the original packaging

Fortuitous Leakage and Waste Disposal Method

In case material is released or spilled, clean up most of the product. Store the residue in plastic tank, neutralize with a solution of caustic soda adjusting pH to 6 - 7, then send to an appropriate water conditioner or call for a specialized company.

Important Notes

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL

Reference No. QS654/010411

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD